

Mutual Materials Firebrick is manufactured to comply with the physical properties and characteristics specified by ASTM C 1261, Standard Specification for Firebox Brick for Residential Fireplaces. They are specifically designed for use in wood inserts or stoves and are not meant for exposed outdoor use, veneer wall or horizontal paving applications.

Mutual Materials firebrick is manufactured from a special blend of clay and shale to produce a hard-fired refractory brick capable of resisting the heat produced in a common fireplace.

Maximum recommended temperature: 2700° F.

Firebrick Standard 9" L x 4 ½" W x 2 ½ H" 22.9 cm L x 11.43 cm W x 6.35 cm H

Product	Dimensions	Color	Wt/ Piece	Wt/Box
Firebrick Standard	<b>9" L x 4</b> ½" <b>W x 2</b> ½" <b>h</b> 22.9 cm L x 11.43 cm W x 6.35 cm H	Buff	<b>6.5 lbs</b> 2.94 kg	<b>25–40 lbs</b> 11–18 kg
Firebrick Split	9"L x 4½"W x 1 ½"h 22.9 cm L x 11.43 cm W x 3.8 cm H	Вип	<b>4 lbs</b> 1.81 kg	



Firebrick Split 9" L x 4 ½" W x 1 ½ H" 22.9 cm L x 11.43 cm W x 3.8 cm H



## **MUTUAL MATERIALS LOCATIONS**

For product information and customer service, call 1-888-MUTUALØ (688-8250).

WASHINGTON		OREGON	IDAHO	MONTANA
Auburn	Port Orchard	Bend	Boise	Missoula
Bellevue	South Seattle	Clackamas	Hayden	
Bellingham	Spokane	Durham		
Marysville	Tacoma (Parkland)	Hillsboro		
Olympia (Tumwater)	Vancouver, WA	Portland	MUTUA	L <b>M</b> ATERIALS
		Salem		Materials.com