

Landstone

2cm Outdoor Porcelain Tile







BC BRICK SUPPLIES LTD.
 MORE THAN JUST A BRICK STORE



These beautiful porcelain tiles are available in 15 natural stone textures and colours. They are ideal for pedestrian walkways, backyard and rooftop patios. Their anti-slip finish and low water absorption feature make them perfect for outdoor applications. They can be installed on many different foundations such as concrete, pedestals and a gravel/sand base.

BST01 Graphite	BST02 Granite	BST03 Slate Grey	SDS02 Arctic Wind	SLG015G Durban Slate
Olivian Black	Quartz Anthracite	Basaltina Grigio	TRV01 Crema Travertine	TRV02 Blanca Travertine
CMT03 Cemento	Sicily Blanco	Sicily Grey	Sicily Nero	Sicily Sand

Sizes				
	12" x 24"	12" x 24" Stair Tread	24" x 24"	24" x 48"
Actual Sizes	300mm x 600mm	300mm x 600mm	600mm x 600mm	600mm x 1200mm
Colours	Granite Graphite Slate Grey	Blanca Travertine Crema Travertine Durban Slate Granite Graphite Slate Grey	Arctic Wind Basaltina Grigio Blanca Travertine Cemento Crema Travertine Durban Slate Granite Graphite Olivian Black Quartz Anthracite Slate Grey Sicily Blanco Sicily Grey Sicily Nero Sicily Sand	Granite Olivian Black Quartz Anthracite

Technical Specifications

	Water Absorption	iso 10545-3	$E \leq 0.5\%$
	Breaking Strength	iso 10545-4	$\geq 810\text{kg/cm}^2$
	Modulus of Rupture	iso 10545-4	$\geq 8000\text{N}$
	Abrasion Resistance	iso 10545-6	145mm^3
	Linear Thermal Expansion	iso 10545-8	$7 \times 10^{-6} / ^\circ\text{C}$
	Thermal Shock Resistance	iso 10545-9	resistant
	Slip Resistance (Oil Wet Ramp Test)	din 51130	R11
	Coefficient Of Friction (C.O.F.)	astm c1028	wet/dry ≥ 0.7
	Chemical Resistance	iso 10545-13	resistant
	Stain Resistance	iso 10545-14	resistant
	Frost Resistance	iso 10545-12	resistant

Contact Us

For further information, please reach out to us at **604-270-1947**
or visit our showroom at **3100 No 5 Rd, Richmond, BC V6X 2T5**
<https://www.bcbrick.com>

